

Effective Date: July 20, 2005

*SPECIFICATIONS

QUALITY: S-099 SAVANNAH - Synthetic Power-Lock® High Performance Backing System

COLORS: (13) 2642 Fort Pulaski 2645 Wrought Iron 2648 Liberty Square
2651 Forsyth Square 2643 Oglethorpe Ave. 2646 SCAD
2649 Tybee Island 2652 Cotton Exchange 2644 Waving Gir
2647 Bay Street 2650 City Market 2653 Mercer House
2654 Emmet Park

CONSTRUCTION - Multi-Level Pattern Loop
PILE FIBER - 100% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield stain and soil protector.
DYE METHOD - Solution Dyed
PRIMARY BACKING - 100% Synthetic
SECONDARY BACKING - Power Lock® High Performance Backing System
YARN PLY - 4 Ply & 2 Ply
TUFTED YARN WEIGHT - 28 Oz. per Sq. Yd. (949 g/m²)
FINISHED PILE THICKNESS - .135 Inch Approx. (3.43 mm)
STITCHES PER INCH - 12 (4.72 stitches/cm)
MACHINE GAUGE - 1/8" (3.15 rows/cm)
DENSITY FACTOR - 7,467
TRAFFIC CLASS - Extra Heavy Commercial Class III
CARPET WIDTH - 12' (3.66 m)
PATTERN REPEAT - 1/2" W x 3/4" L (1.27 cm W x 1.91 cm L)
DYE LOT SIZE - 20,000 Square Yards
VETTERMAN DRUM-WEAR - 3-4 or better after 22,000 cycles - ASTM 5417
DELAMINATION - 2.70 Lbs/Inch or Greater - ASTM D3936
LIGHT FASTNESS - 4 or Better After 8 Cycles of Exposure - AATCC 16
OZONE - 4 or Better After 8 Cycles of Exposure - AATCC 129
OXIDES OF NITROGEN - 4 or Better After 8 Cycles of Exposure - AATCC 164
FLAMMABILITY - ASTM E-648 - Class INFPA 258 - 450 or Less

WARRANTIES:

| | | |
|-------------------------------------------|---|----------------------------------------------|
| EDGE RAVEL GUARANTEE | - | Useful Life |
| DELAMINATION GUARANTEE | - | Useful Life |
| RUN RESISTANCE WARRANTY | - | Useful Life |
| WEAR WARRANTY | - | Useful Life |
| STAIN REMOVAL GUARANTEE | - | Useful Life |
| STATIC WARRANTY | - | Useful Life |
| COLORFASTNESS TO LIGHT- | - | Useful Life |
| COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS | - | Useful Life |
| RECYCLING PROGRAM | - | Qualifies for 6ix [®] Again Program |

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 4079

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Savannah requires the row cut seaming technique in order to produce quality seams (leave low row on one edge, cut off low row on adjacent edge). Seam sealer must be used.

Carpet must be installed according to manufacturer's carpet installation procedures.