

***SPECIFICATIONS**

QUALITY: 6900 SOUNDS

| | | |
|--------------------|-------------|---------------|
| COLORS (8): | 6902 Chorus | 6906 Octave |
| | 6903 Scale | 6907 Harmonic |
| | 6904 Rhythm | 6908 Minor |
| | 6905 Chord | 6909 Major |

| | | |
|--------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------|
| CONSTRUCTION | - | Tip Shear Pattern Loop |
| YARN | - | SEP* Solution Dyed Nylon and Yarn Dyed Nylon w/Antistat |
| TUFTED YARN WEIGHT | - | 24 Ounces (814g/m ²) |
| MACHINE GAUGE | - | 1/12" (4.72 rows/cm) |
| STITCHES PER INCH | - | 12 (4.72 stitches/cm) |
| FINISHED PILE THICKNESS | - | .147 (3.73mm) |
| WIDTH | - | 12 ft. (3.66 m) |
| DYE METHOD | - | Solution Dyed/Yarn Dyed |
| SOIL/STAIN PROTECTION | - | Blue Shield® Soil and Stain Protector |
| DENSITY | - | 5878 |
| CRI TRAFFIC RATING | - | Heavy |
| SECONDARY BACKING | - | Woven Synthetic |
| RADIANT PANEL TEST | - | Class I |
| NBS SMOKE CHAMBER TEST | - | Passes |
| COORDINATING STYLES | - | Lights, Homecoming |
| PATTERN REPEAT | - | ¼" W x 4 ¾" L (.635 cm W x 12.07 cm L) |
| OPTIONAL BACKINGS | - | High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details. |
| WARRANTIES | - | 10-Year Wear Warranty 10-Year Delamination Warranty 10-Year Edge Ravel Warranty |

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

*S.E.P. Nylon is: Solution dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.