

# Blueridge MODULAR

## \*SPECIFICATIONS

<b>QUALITY:</b>	<b>T-618T TRAVELER</b>	24" X 24" Carpet Tile	
	<b>T-618V TRAVELER</b>	6 Ft. EnviroFlex®	
<b>COLORS:</b>	2740 Doughton Park	2744 Lost Core	2748 Elk River
	2741 Gum Tree	2745 Hawks Bill	2749 Timber Ridge
	2742 Glen Burney	2746 Flattop Mountain	2750 Air Bellows
	2743 Crabtree Meadows	2747 Iron Mountain	2751 Fontana Lake
<b>CONSTRUCTION</b>	-	Multi-Level Pattern Loop	
<b>YARN</b>	-	100% Antron Lumena® Solution Dyed Nylon with Dura Tech® Soil Resistant Treatment and Recycled Content	
<b>BENEFITS</b>	-	Antron® Lumena Solution Dyed Nylon carpet face fiber has a 30% lower total environmental impact than typical industry. DuraTech® Soil resistant treatment provides superior soil resistance durable for the useful life of the carpet.	
<b>DYE METHOD</b>	-	Solution Dyed	
<b>PRIMARY BACKING</b>	-	100% Synthetic	
<b>SECONDARY BACKING</b>	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content	
<b>TUFTED YARN WEIGHT</b>	-	20 Ounces Per Sq. Yd. (678 g/m <sup>2</sup> )	
<b>TOTAL WEIGHT</b>	-	Approximately 144 Ounces Per Sq. Yd. (4882 g/m <sup>2</sup> )	
<b>FINISHED PILE THICKNESS</b>	-	Approximately .128 inch (3.25 mm)	
<b>STITCHES PER INCH</b>	-	10 (3.94 stitches/cm)	
<b>MACHINE GAUGE</b>	-	1/12" (4.72 rows/cm)	
<b>DENSITY FACTOR</b>	-	5625	
<b>TILE SIZE</b>	-	24" X 24" (60.96 cm X 60.96 cm)	
<b>ROLL WIDTH</b>	-	6 Ft. (1.83 cm)	
<b>CRI TRAFFIC RATING</b>	-	Severe	
<b>PATTERN REPEAT</b>	-	18" W x 26" L (45.72 cm W x 66.04 cm L)	
<b>ADHESIVES</b>	-	BR200 EnviroFlex® Modular Carpet Adhesive	
Installation	-	Monolithic or ¼ Turn	
Wear Warranty	-	Useful Life	
Edge Ravel Guarantee	-	Useful Life	
Delamination Guarantee	-	Useful Life	
Run Resistance Warranty	-	Useful Life	
Stain Removal Guarantee	-	Useful Life	
Static Warranty	-	Useful Life	
Colorfastness to Light	-	10 Year	
Colorfastness to Atmospheric Contaminants	-	5 Year	
Recycling Program	-	Qualifies for Invista Reclamation Program	

### **NOTES:**

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Carpet must be installed according to manufacturer's carpet installation procedures. Seam sealer must be used with 6 ft. rolls.