

Effective Date: March 17, 2000

\*SPECIFICATIONS

QUALITY: W-385 WELLINGTON

COLORS:

9368 Admiral Blue	9369 Blue Morn	9370 Southern Sky	9371 Early Dusk
9372 Gulf Shore	9373 Tropic Jade	9374 Plum Wine	9375 Dark Violet
9376 Lilac Grey	9377 Mountain Green	9378 Fox Hunt	9379 Willow Park
9380 Zinfandel	9381 Casino Red	9382 Granite Rose	9383 After Dark
9384 Winter Cloud	9385 Lancaster	9386 Miami Spice	9387 Warm Clay
9388 Mineral Beige	9389 Olive Branch	9390 Outback	9391 Temple Sand

CONSTRUCTION	-	Multi-Level Textured Cut and Loop
PILE FIBER	-	100% Invista XTI Continuous Filament BCF Nylon with Static Control. Treated with a Stain Protector and a Fluorocarbon Soil Repellent.
YARN PLY	-	2 Ply Tightly Twisted and Heat Set
TUFTED YARN WEIGHT	-	36 ozs. per sq. yd. (1220 g/m <sup>2</sup> )
MACHINE GAUGE	-	1/8" (3.15 rows/cm)
STITCHES PER INCH	-	13 (5.12 stitches/cm)
FINISHED PILE THICKNESS	-	.222 inch approx. (5.64 mm)
DENSITY FACTOR	-	5,838
WIDTH	-	12' (3.66 m)
PRIMARY BACKING	-	Woven Synthetic
SECONDARY BACKING	-	Synthetic
DYE LOT SIZE	-	Approx. 1,000 square yards
PATTERN REPEAT	-	3/4" Wide x 1" Long (1.95 cm x 2.54 cm)
FLAMMABILITY	-	Average Critical Radiant Flux: Greater than .22 – Class II
NBS SMOKE CHAMBER TEST		
CARPET TESTING PROGRAM	-	Specific Optical Density: Less than 450
TRAFFIC CLASS	-	Extra Heavy Commercial Class III

WARRANTIES:

Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Wear Warranty	-	Useful Life
Static Warranty	-	Useful Life
Recycling Program	-	Qualifies for 6ix Again® Program

CRI – INDOOR AIR QUALITY CARPET TESTING PROGRAM – Passes – Certification No.  
14222878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

\*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Carpet must be installed according to manufacturers carpet installation procedures. Seam sealer must be used.

As with all patterned carpet, perfect match may not be obtainable at seams.